





HSF





产品放置




No. 1
产品装入真空盒内
真空盒规格:SB-14AB(310*270*13MM)





No. 2
盖上盒盖并四边六处钉上订书针





No. 3
贴标签于真空盒左上角




No. 4
纸箱内需套防水袋PE-19, 再将真空盒装入纸箱(24盒/箱)
加一包干燥剂后真空密封
纸箱规格:CTN-73K(双坑K=K, 32*28*36CM)




No. 5
封箱及贴标签于纸箱侧面的左上角



No. 6
打包装带



贴外箱标签及ROHS标签



PE-19

2.54 牛角 180度 金属短耳扣

规格	真空盒装数量	每箱装总数量	规格	真空盒装数量	每箱装总数量
6P	170	4080	26P	60	1440
8P	150	3600	30P	50	1200
10P	130	3120	34P	50	1200
12P	110	2640	40P	40	960
14P	100	2400	44P	40	960
16P	90	2160	50P	30	720
20P	80	1920	60P	30	720
24P	70	1680	64P	30	720

说明:

1. 产品如图所示型态放入真空盒
2. 注意各标签样式、位置及方向的一致性;
3. 打外箱包装带时需注意, 打为十字型。

变更记事

版次 REV	日期 DATE	变更说明 MODIFICATION DESCRIPTION	变更 CHANGE	核准 APPROVE	零件图	颜色 COLOR	材质 MATERIAL	设计 DESING	审核 CHECK	核准 核 准	SCALE	fit
A1	2010/08/25	变更包装规范 (加套防水袋)			X. ±0.50			马云青	10/08/25		UNIT	mm
A0	2007/07/10	NEW			X.X ±0.20						SIZE	A4
					X.XXX ±0.10						SHEET	1/1
					Angle						PROJ.	
					X. ± 2'							
					DIM							
					TOL							

WCON

WCON Hardware Electronics Co., Ltd

料号 PART NO. 3211-XXSXXSA1

品名 TITLE: 2.54牛角 180度 金属短耳扣 包装规范